



BORN FOR SAFETY

Intrinsically Safe DMR Portable Two-way Radio

HP79XEx IIA



For workers in the Oil and Gas industry or firefighters in the Fire and Rescue, they operate in extreme conditions and take risks from explosive gas, combustible dusts, or chemical vapors. In the dangerous environments, safe, reliable, and high-efficient communication is paramount.

The HP79XEx IIA intrinsically safe DMR portable two-way radio leverages Hytera's 20 years of experience and expertise in explosion protection to take personal safety and mission-critical communications to a new level for the workers in oil and gas, mining, chemical, pharmaceuticals, and other industries with hazardous environments.

Certified with IECEx/ATEX, the HP79XEx IIA is the safest radio to keep the workers connected in hazardous environments without causing a fire or explosion. HP79XEx IIA has IS circuit, long-lasting explosion-proof battery, superior audio, extended radio coverage, and advanced ergonomics for easy operation.






Fire and Rescue

When firefighters make efforts to protect lives and properties in a place full of smoke, dust, and even toxic gas, the HP79XEx IIA provides safe and effective communications for them.



Oil and Gas

In dangerous environments with flammable liquid and explosive gas, the HP79XEx IIA ensures stable communications for operators to ensure their safety.



Mining

When miners work in complex coal wells with various explosive gases and combustible dust, such as methane, the HP79XEx IIA helps them stay connected and safe.



Manufacturing

In pharmaceutical processing, steel plant, food processing, and more industries where the chances of massive dust explosions are high, the HP79XEx IIA with a higher IS level can keep the workers safe by reliable communications.



Airport

In the airport with complex facilities that are exposed to fuels, the HP79XEx IIA offers the staff and on-site fire crew with instant and efficient communications.



Chemical Plant

In the chemical plant where the conversion and processing of flammable gases, liquids, and solids may lead to explosion, the HP79XEx IIA ensures stable communications for safe production.



ULTIMATE SAFETY

The HP79XEx IIA intrinsically safe radio is certified to standards listed by IECEx. It has been developed to provide safe and reliable communication in hazardous environments by adopting the new materials, brand-new structural design and innovative IS circuit. With optimized RF solution and pioneering audio solution, it extends communication range and provides better audio. Moreover, the HP79XEx IIA prepares for the unexpected before it really happens, thanks to lone worker, man down, and precise positioning.

IECEx

Ex ib I Mb
Ex ib IIA T4 Gb
Ex ib IIIC T120°C Db
IP66/IP67/IP68, -25°C≤Ta≤+50°C

ATEX


I M2 Ex ib I Mb
II 2G Ex ib IIA T4 Gb
II 2D Ex ib IIIC T120°C Db
IP66/IP67/IP68, -25°C≤Ta≤+50°C

US

Class I, Zone 1, AEx ib IIA T4 Gb
Zone 21, AEx ib IIIC T120°C Db
IP66/IP67/IP68, -25°C≤Ta≤+50°C

CA

Ex ib IIA T4 Gb
Ex ib IIIC T120°C Db
IP66/IP67/IP68, -25°C≤Ta≤+50°C



- Equipment group:
I: Mining
II: Other Environments (non-mining: chemical industrials, oil refineries, etc.)
- Explosive atmospheres
G: Gases, vapors and mist
D: Dusts
- Level of Protection:
ia: Intrinsically safe (Zone 0/1/2)
ib: Intrinsically safe (Zone 1/2)
- Temperature Class
T1: 450°C
T2: 300°C
T3: 200°C
T4: 135°C
T5: 100°C
T6: 85°C
- Dust & Water Ingress Protection

II 2G Ex ib IIA T4 IP66/IP67/IP68 GAS

- Explosion-proof Standard:
EU ATEX directive and IECEx standards
- Gas Group:
I: Methane (Mining)
IIA: Propane
IIB: Ethylene
IIC: Acetylene, hydrogen
(Hazard Level: IIC>IIB>IIA)
- Classification for hazardous places
1: Very high level (zone 0 or zone 20)
2: High level (zone 1 or zone 21)
3: Normal level (zone 2 or zone 22)
Zone 0: present continuously
Zone 1: present intermittently
Zone 2: present abnormally

- Equipment group:
I: Mining
II: Other Environments (non-mining: chemical industrials, oil refineries, etc.)
- Explosive atmospheres
G: Gases, vapors and mist
D: Dusts
- Level of Protection:
ia: Intrinsically safe (Zone 20/21/22)
ib: Intrinsically safe (Zone 21/22)

DUST II 2D Ex ib IIIC T120°C IP66/IP67/IP68

- Explosion-proof Standard:
EU ATEX directive and IECEx standards
- Dust Group:
IIIA: combustible flyings
IIIB: non-conductive dust
IIIC: conductive dust
- Temperature Class
T120°C
- Dust & Water Ingress Protection
- Classification for hazardous places
1: Very high level (zone 0 or zone 20)
2: High level (zone 1 or zone 21)
3: Normal level (zone 2 or zone 22)
Zone 0: present continuously
Zone 1: present intermittently
Zone 2: present abnormally

- Equipment group:
I: Mining
II: Other Environments (non-mining: chemical industrials, oil refineries, etc.)
- Explosion-proof Standard:
EU ATEX directive and IECEx standards
- Dust & Water Ingress Protection

I M2 Ex ib IP66/IP67/IP68 MINING

- M1: Equipment must continue to operate in a potentially explosive environment.
M2: Equipment does not operate in a potentially explosive environment. (Hazard Level: M1>M2)
- Level of Protection:
ia: Intrinsically safe (Category M1/M2)
ib: Intrinsically safe (Category M2)



Born for Safety




Wider range of operation temperature (in Ex area)

Thanks to new explosion-proof materials and advanced mechanical design, the HP79XEx IIA is built to work under temperatures from -25°C to 50°C in explosion-prone areas. With stable and even heat dissipation, the HP79XEx IIA is engineered to work in the extreme conditions, bringing extra safety and efficiency to everyday work.



More powerful intrinsically safe circuit

The HP79XEx IIA adopts innovative silicone encapsulation technology to prevent liquid, inflammable dust, or explosive gas from intruding internal circuits. With multiple circuit protection mechanisms, the HP79XEx IIA strictly limits the electrical circuit's energy to a non-ignitable level during operation. Meanwhile, the circuit contributes to 5W(VHF) TX power and 2-watt audio power, extending the communications distance and boosting the audio loudness.



More rock-solid IS battery

The IS battery is secured to the radio by battery protection plate and an anti-falling battery latch. Even if the HP79XEx IIA is dropped by accident, the battery will never become detached to avoid potential sparks in hazardous circumstances. In addition, the HP79XEx IIA is forbidden to be used with non-original battery with prompt on screen and flashing red LED indicator, as the safety of life and property cannot be endangered by any risks.

More professional anti-static technology

Electrostatic discharges are a source of ignition in explosive risk areas. Taking this in mind, the HP79XEx IIA first adopts high-strength, explosion-proof materials to prevent static electricity on the surface. Then the HP79XEx IIA uses a dual-material technology to resist the build-up of static electricity. So the workers can freely use the HP79XEx IIA without worrying the threats to lives and properties from the brisk fire or massive explosion.





Reliable to Use



Rugged-tested trust

The HP79XEx IIA is certificated with IP6X and MIL-STD-810H after a whole list of reliability tests such as accelerated life testing, impact test for the radio with 2.4-inch screen, and drop test. It is rugged enough to withstand dust, shock, or sudden drop. The workers can use the radio whatever harsh environments they encounter.



Dual antimagnetic mechanism

In the area containing metallic compounds, the HP79XEx IIA resists magnetic metal dust and shavings from the environments to damage the speaker — ensuring more outstanding audio and longer service life. All lies in the dual antimagnetic mechanism.





Built for Personnel Safety



Lone worker

Lone Worker provides protection and reassurance for those who work alone especially in dangerous environments, such as oil pipeline walker. If the HP79XEx IIA senses that the worker does not make any operation within a preset time, this radio will automatically alarm and report the location to the companion or control center for help.



Man down

Man Down is ideal for emergency situation. If the worker has fallen or is unconscious, or is unable to move, the HP79XEx IIA automatically detects a sudden tilt towards the ground, and alarms and reports the location to the companion or control center for help. This is vital to prevent loss of life and dangers.



Precise positioning

With the built-in positioning module, the HP79XEx IIA supports the flexible combination of GPS, BDS, GLONASS and Galileo satellite systems. Also, the HP79XEx IIA enhances positioning accuracy down to one meter, thanks to the dual-frequency positioning technology. Such reliable and accurate location information helps find the worker in need of assistance quickly in emergencies.





HIGH EFFICIENCY COMMUNICATIONS

The HP79XEx IIA takes critical communications to a new level, with the efforts of Hytera Audio Lab, RF & Antenna Lab, Energy-efficient Lab, and UX Design Lab*. The HP79XEx IIA keeps the workers always connected, from superior audio quality to extended radio range. The HP79XEx IIA is always in uptime thanks to the long-lasting battery. Moreover, the HP79XEx IIA facilitates the usage and management in terms of versatile connectivity and easy-to-use design.

* Hytera Professional Lab.



Superior Audio Quality

Super loudness

Most explosion-prone environments are noisy, thus how to provide clear and loud audio is the key to ensure effective communication among team members. The HP79XEx IIA, with a lighter and slimmer body, has a 2W speaker to deliver louder audio to improve team collaboration and work efficiency.

Ultra Clarity

With cutting-edge audio processing technology adopted, the HP79XEx IIA delivers crisp, clear audio even in complex environments, ensuring more reliable mission-critical and business-critical communications.

AI-based noise cancellation

The HP79XEx IIA adopts the most advanced AI-based noise cancellation algorithm and gets machine learning behavior. After learning and training thousands of noise samples, the HP79XEx IIA can quickly separate the human voice from the noise, making the workers get the right commands from the first word.

Water-porting design

The speaker has a unique water-porting design that can automatically expel water from the speaker's acoustic cavity fast. Even in heavy downpours, the HP79XEx IIA can still deliver clear audio.

Automatic gain control

Automatic gain control (AGC) automatically increases or decreases microphone gain to ensure consistently loud and clear audio output, regardless of how softly or loudly the workers are talking into the microphone.

Howling suppression

Using the innovative howling suppression algorithm, the HP79XEx IIA eliminates a screeching feedback sound when two radios are too close, even 30 cm away from each other.





Long-lasting Battery

The standard 2150 mAh battery, together with the cutting-edge low power consumption technology, can outlast the shift. The workers can check the remaining battery and battery health on the radio and extend the battery life using the smart charger.



Extended Radio Range

Thanks to the new-designed powerful IS circuits and RF optimization solution, HP79XEx IIA features 5W(VHF) transmitting power and industry-leading receiving sensitivity (0.16μV), providing more smooth communications even at a distance or in the edge area, further enhancing personal safety and work efficiency.



Versatile Connectivity



BT 5.3

The HP79XEx IIA can connect to wireless IS accessories* more quickly and stably, without the hassle of wires and cables. Moreover, the HP79XEx IIA can run the BT-based applications developed by the third party to meet more scenarios.

* Not provided by Hytera.
The radio adapts the third-party wireless IS accessories.



WLAN

The HP79XEx IIA facilitates remote management through the WLAN, such as programming, upgrading*, and log management*. It is a smarter way to manage radios in batch without getting them back and forth between the field and the office, greatly reducing operational expenses.

* Coming soon.



NFC

The HP79XEx IIA can be easily recognized and managed via NFC tag as per actual requirements.

Easy to Use

About 390g (with standard battery and antenna)

- Comfortable for long-time grip

2.4-inch LCD screen

- Intuitive to operate the radio or view the info

Textured housing on the back

- Never slip down from your fingers



U-shaped groove

- Quick to attach and release the belt clip

Large LED indicator

- Easy to get the radio status

Vibration pattern

- Never miss any call and message



User-friendly UI

- 9-grid menu
- Conversational SMS interface
- Pop-up notification on home screen

Purpose-built knob and keys

- Volume/channel selector knob
- Enlarged emergency key
- Three programmable keys
- Tactile and textured keys
- Four navigation keys



At a Glance

LED Indicator

Channel/Volume Knob

Microphone

2.4-Inch Display

Accessory Connector

Speaker

Emergency Button

Battery Lock

Belt Clip Groove

Strap Hole

Programmable Key

PTT Key

Programmable Keys

NFC Tag

Li-ion Battery



SPECIFICATIONS

General	
Frequency Range	400-480MHz 136-174MHz
Channel Capacity	1024
Zone Capacity	64
Channel Spacing	12.5kHz/20kHz/25kHz
Operating Voltage	7.4V (rated)
Battery	2,150 mAh IIC intrinsically safe Li battery (Typical)
Battery Life (5/5/90)	22h (GNSS OFF) 19h (GNSS ON)
Frequency Stability	±0.5ppm
Antenna Impedance	50Ω
Dimensions (H x W x D)	130 x 55 x 37mm
Weight (with antenna & battery)	about 390g
Display	2.4 inch LCD, 320 x240 pixel, 262000 colors
Connectivity	BT 5.3 BLE+EDR/WLAN 2.4G/NFC: ISO/IEC 15693

Receiver	
Sensitivity	Analog: 0.16uV(12dB SINAD) 0.14uV(Typical)(12dB SINAD) Digital: 0.16uV/BER5%
Adjacent Channel Selectivity	TIA-603: 60dB@12.5kHz; 70dB@20/25kHz ETSI: 60dB@12.5kHz; 70dB@20/25kHz
Intermodulation	TIA-603: 70dB@12.5/20/25kHz ETSI: 65dB@12.5/20/25kHz
Spurious Response Rejection	TIA-603: 70dB@12.5/20/25kHz ETSI: 70dB@12.5/20/25kHz
Blocking	TIA-603: 80dB ETSI: 84dB
Hum and Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz
Rated Audio Power Output	0.5W
Rated Audio Distortion	≤3%
Audio Response	+1 ~ -3dB
Conducted Spurious Emission	<-57dBm

Transmitter	
RF Power Output	UHF: 4W/1W; VHF: 5W/1W
FM Modulation	11K0F3E@12.5kHz 14K0F3E@20kHz 16K0F3E@25kHz
4FSK Digital Modulation	12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm < 1GHz; -30dBm > 1GHz
Modulation Limiting	±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@25kHz
FM Hum & Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz
Adjacent Channel Power	60dB@12.5kHz; 70dB@20/25kHz
Audio Response	+1 to -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE+2™
Digital Protoca	ETSITS102 361-1, -2, -3

Environmental	
Operating Temperature	-30°C to +60°C (in non-hazardous area) -25°C to +50°C (in hazardous area)
Storage Temperature	-40°C ~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air)
Dustproof & Waterproof	IP64/IP65/IP66/IP67/IP68 per IEC-60079-0:2017 & IEC-60529
Humidity	MIL-STD-810H
Shock and Vibration	MIL-STD-810H

Location Services	
GNSS	GPS, BDS, GLONASS, Galileo
TTF(TIME TO FIRST FIX) Cold Start	<35 seconds
TTF(TIME TO FIRST FIX) Hot Start	<1 second
Horizontal Accuracy	1 m (dual-frequency GNSS, 95% probable, -130 dBm, ≥ 22 operational satellites)

Accuracy specs are for long-term tracking (95th percentile values>5 satellites visible at a nominal -130dBm signal strength)

Standard Accessories



Battery (Standard Capacity)



Charger



Power Adapter



Antenna



Belt Clip



Strap

Optional Accessories



Remote speaker Microphone



Earpiece



Carry Case



Intrinsically Safe Hamlet Heavy Duty Noise-cancelling Headset kit



Intrinsically Safe and Adjustable Earset



Intrinsically Safe Large PTT



Hytera Communications Corporation Limited

Stock Code: 002583.SZ

Address: Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, P.R.C.

Tel: +86-755-2697 2999 **Fax:** +86-755-8613 7139 **Post:** 518057

Http://www.hytera.com **marketing@hytera.com**



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd.
©2023 Hytera Communications Corp., Ltd. All Rights Reserved.